

EcoTect® Packaging Board

With a smooth surface for image fidelity and a brightness that makes images and colors pop, Sonoco's EcoTect® packaging board offers consistently high print quality, and is compatible with both flexographic and offset printing. With a lower density per caliper than comparable clay-coated paperboard (CRB), EcoTect packaging board offers cost savings of 15-35%, on average.

EcoTect packaging board is also an environmentally responsible option, made from 100% recycled fibers.

EcoTect grades are available as chain-of-custody certified to any of the three fiber certification programs. Learn more at www.sonoco.com/environment.



Typical Test Values:

EcoTect URB

Caliper (inch)	.016	.018	.020	.022	.024	.026	.028
Basis weight (#/MSF)	57.6	64.8	72	79.2	86.4	88.4	95.2
Density (#/Point)	3.6	3.6	3.6	3.6	3.6	3.4	3.4
Stiffness MD (Taber)	115	180	245	310	375	441	506
Stiffness CD (Taber)	39	64	88	112	137	161	185
Sheffield Smoothness Top	340	350	360	370	380	385	395
Caliper Metric (Micron)	406	457	508	559	610	660	711
Basis Weight Metric GSM	281	316	352	387	422	432	465

Product is sized to a 70-second target using a 2-minute TAPPI Cobb test
Additional caliper options available upon request